

GRANITE TOP PIZZA PREP TABLES



**5 YEAR
WARRANTY**

Parts & Labor - 7 YEAR COMPRESSOR



IRT-MPG1980 COMBO



InfricoUSA

Infrico

USA

INFRICO USA CORP
11200 NW 25th Street STE 123
Sweetwater, FL 33172
305-777-9599
sales@infrico.com



BIM | CAD | MOBILE

GRANITE TOP PIZZA PREP TABLES

GENERAL FEATURES

HIGHER ENERGY EFFICIENCY

R290 refrigerant with electric fans and evaporative tray without electric resistances.

SANITATION

Quick and easy removal of the shelves and slides for interior cleaning.

DISPLAY CASE

Refrigerated ingredient case with glass lid and stainless steel pans included.

CONTROL SYSTEM

Greater ability for temperature adjustments to meet each end-user requirements.

100% TESTED

All condensing units undergo rigorous testing in helium chambers for refrigerant leak detection and a final equipment test in a state-of-the-art test room.

CERTIFIED

Audited and Certified by INTERTEK for compliance with UL 471 and NSF 7.

STANDARD FEATURES

EXTERIOR - INTERIOR

- AISI 304 Stainless Steel with granite worktop.
- Internal drain plug for easy cleaning. Sealed interior floors and rounded cabinet corners

DOOR

- Polyurethane insulated door.
- Self-closing door with stay open feature.
- Stainless Steel heavy-duty hinges.
- Four chamber snap in door gaskets for easy removal and cleaning.
- Door opening: 14-3/4" x 20-5/8".

INSULATION

- CFC- Free polyurethane insulation, entire cabinet structure is foamed-in using a high-density polyurethane insulation.
- Low GWP & Zero ODP effect.

SHELVING

- One plastic coated wire shelves per door with stainless steel tray slides included. Easy remove for cleaning.

REFRIGERATION

- Digital temperature controller with automatic defrost system.
- Front-breathing refrigeration system.
- Forced air refrigeration system.
- Extractable condensing unit for easy service.
- Evaporator coil coated with anti-corrosion material 100% polyester.
- Refrigeration system is independent for table and ingredient case.



MODEL	OVERALL DIMENSIONS		DOORS	SHELVES	(F°)	(FT³)	(HP)	115V	(LBS)	DOE (Hydrocarbon)	
IRT-MR67-GT COMBO	68 - 7/8	32 - 5/8	59 - 3/8	2	4/15	33°F/43°F	17	3/8	4.76	955	R-290
			17 - 3/4	-	-	30.2°F/44.6°F	1.83	1/8	1.82		R-600a
IRT-MR93-GT COMBO	93 - 1/4	32 - 5/8	60 - 3/4	3	4/15	33°F/43°F	27	1/2	4.76	1260	R-290
			17 - 3/4	-	-	30.2°F/44.6°F	2.86	1/8	1.82		R-600a
IRT-MPG1490 COMBO	58 - 3/4	27 - 1/2	42 - 7/8	2	2/10	33°F/43°F	10.77	1/4	3.53	681	R-290
			17 - 1/2	-	-	30.2°F/44.6°F	1.30	1/6	1.84		R-600a
IRT-MPG1980 COMBO	60 - 1/8	27 - 1/2	42 - 7/8	3	3/15	33°F/43°F	16.42	1/4	4.76	813	R-290
			17 - 1/4	-	-	30.2°F/44.6°F	2.36	1/6	1.82		R-600a